

Sipwise NGCP Administration Interface

administrator
logout (/logout)
Information (#)
User Administration (#)
System Administration (#) <u>Domains (/domain)</u> <u>Administrators (/admin)</u> <u>Billing (/billing)</u> <u>SIP Peerings (/peering)</u> <u>Rewrite Rule Sets (/rewrite)</u> <u>Sound Sets (/sound)</u> <u>Security Bans (/bans/users)</u>
Number Management (#)

Peer Host Vitelity 28 Preferences

[\(detail?group_id=2\)](#) [\(preferences?peerid=3&edit_preferences=1\)](#)

- peer_auth_user:

- peer_auth_pass:

<input type="text"/>
• peer_auth_realm: <input type="text"/>
• peer_auth_register: <input type="checkbox"/>
• concurrent_max: <input type="text"/>
• concurrent_max_out: <input type="text"/>
• force_outbound_calls_to_peer: <input type="checkbox"/>
• find_subscriber_by_uuid: <input type="checkbox"/>
• rewrite_rule_set: <input type="text"/>
• sst_enable: <input type="text" value="no"/>
• sst_expires: <input type="text"/>
• sst_min_timer: <input type="text"/>
• sst_max_timer:

• sst_refresh_method:
<input type="text" value="UPDATE_FALLBACK_INVITE"/>
• outbound_socket:
<input type="text" value="default"/>
• inbound_upn:
<input type="text" value="From-Username"/>
• inbound_npn:
<input type="text" value="From-Username"/>
• outbound_from_user:
<input type="text" value="User-Provided-Number"/>
• outbound_from_display:
<input type="text" value="None"/>
• outbound_pai_user:
<input type="text" value="Network-Provided-Number"/>
• outbound_ppi_user:
<input type="text" value="None"/>
• inbound_uprn:
<input type="text" value="None"/>
• outbound_diversion:
<input type="text" value="None"/>
• ip_header:

- use_rtpmproxy:

Always with plain SDP ▼
- ipv46_for_rtpmproxy:

Auto-detect ▼

NGCP www_admin version 3.6.3 - Copyright 2007-2012 Sipwise GmbH, Austria.

www.sipwise.com (<http://sipwise.com/>)